










# Hypra<sup>®</sup> IP 66/67-55 plastic - increased safety


LV 16 to 125 A

63 A and 125 A  
easy connection  
disconnection


Conform to IEC 60309-1 and IEC 60309-2 IP according to IEC 60529 IK 09: Plastic Self-extinguishing: 850°C (support of active parts) / 650°C (plastic housing)			FUNCTIONS									
			Panel mounting sockets		Surface mounting sockets	Through wiring surface mounting sockets	Straight plugs	Angled plugs	Mobile sockets	Surface appliance inlets	Straight panel appliance inlets	Socket with break isolating switch
			 Female connector		 Female connector	 Female connector	 Male connector	 Male connector	 Female connector	 Male connector	 Male connector	 Female connector
LV	inclined outlets	with single fixing centres										
200 to 250 V <sub>~</sub> 50/60 Hz	16 A	2P+E	0 511 26 <sup>(1)</sup>	0 511 46	0 511 26 + 0 520 29 <sup>(1)</sup>	0 511 26 + 0 520 89	0 511 56 <sup>(1)</sup>	0 511 06	0 511 76	0 511 86	-	-
	32 A	2P+E	-	0 530 46	0 530 46 + 0 529 40	0 530 46 + 0 529 90	0 530 56	0 530 06	0 530 76	0 530 86	-	-
380 to 415 V <sub>~</sub> 50/60 Hz	16 A	3P+E	0 511 30	0 511 50	0 511 30 + 0 522 29 <sup>(1)</sup>	0 511 30 + 0 522 89	0 511 60 <sup>(1)</sup>	0 511 10	0 511 80	0 511 90	-	-
		3P+N+E	0 511 31	0 511 51	0 511 31 + 0 522 29 <sup>(1)</sup>	0 511 31 + 0 522 89	0 511 61 <sup>(1)</sup>	0 511 11	0 511 81	0 511 91	-	-
	32 A	3P+E	-	0 530 50	0 530 50 + 0 529 40	0 530 50 + 0 529 90	0 530 60	0 530 10	0 530 80	0 530 90	-	-
		3P+N+E	-	0 530 51	0 530 51 + 0 529 40	0 530 51 + 0 529 90	0 530 61	0 530 11	0 530 81	0 530 91	-	-
	63 A	3P+E	0 594 27	-	0 594 37	0 594 27 + 0 538 89	0 594 47	-	0 594 87	-	0 594 77 <sup>(2)</sup>	-
		3P+N+E	0 594 28	-	0 594 38	0 594 28 + 0 538 89	0 594 48	-	0 594 88	-	0 594 78 <sup>(2)</sup>	-
125 A	3P+E	0 595 12	-	0 595 02	-	0 595 22	-	0 595 32	-	0 595 42	0 591 14	
	3P+N+E	0 595 13	-	0 595 03	-	0 595 23	-	0 595 33	-	0 595 43	0 591 15	

Pack = 1 except 1: pack = 5  
 2: Can be fixed on Cat.No 0 538 89 to obtain a straight surface mounting appliance inlet


## Complete range from 16 A to 125 A: IP 55 (minimum) guaranteed



When connected: IP 55 guaranteed with the cover closed on the plug (with a pair of Hypra IP 66/67-55 products)



IP 66/67 obtained with the ring locked



When not connected IP 55 assured when cover is closed; IP 66/67 obtained with the ring locked