

## PSEN ml b 1.1 unit

570400



Safety gate system with mechanical guard locking, basic version, IP67, 8pin M12 pigtail 230mm; 4 LEDs on 3 sides; Applications up to SIL3/PL e/ Cat4; Content = 1 coded Sensor with actuator.

## Technical details

Approvals:	CE;cULus Listed;TÜV;FCC;IC
Sensor principle:	Transponder
Type of coding:	Coded
Number of OSSD outputs:	2
Connection type:	M12, 8pol. male
Supply voltage (V):	24,0
Power consumption DC:	1.0 W
Supply voltage type:	DC
Protection type, housing:	IP67
Coding level EN ISO 14119 aligned:	gering
Width dimension:	40.0 mm
Height dimension:	217.2 mm
Depth dimension:	40.0 mm
Gross weight:	1450 g
Net weight:	1100 g
Ambient temperature:	0 - 60 °C

## Optional accessories



540319

PSEN cable axial M12 8-pole 3m



540320

PSEN cable axial M12 8-pole 5m



540321

PSEN cable axial M12 8-pole 10m



540326

PSEN cable axial M12 8-pole 30m



540340

PSEN cable M12-8sf M12-8sm, 2m



540341

PSEN cable M12-8sf M12-8sm, 5m



540343

PSEN cable M12-8sf M12-8sm, 20m



540344

PSEN cable M12-8sf M12-8sm, 30m



540342

PSEN cable M12-8sf M12-8sm, 10m



540333

PSEN cable M12-8sf, 20m

	540347	PSEN cable M12-8sf M12-8sm, 1,5m
	540345	PSEN cable M12-8sf M12-8sm, 0,5m
	540346	PSEN cable M12-8sf M12-8sm, 1m
	570490	PSEN ml mounting plate
	570492	PSEN ml bracket sliding door
	570495	PSEN ml door handle sliding door
	570496	PSEN ml door handle swinging door 70
	570497	PSEN ml door handle swinging door 80
	570493	PSEN ml bracket swinging door 70



570494

PSEN ml bracket swinging door 80



570499

PSEN screw set bracket sliding door



570498

PSEN screw set bracket swinging door



570462

PSEN ml escape release extension



570471

PSEN ml escape release cordset 2,0m



570474

PSEN ml escape release cordset 3,5m



570472

PSEN ml escape release cordset 2,5m



570470

PSEN ml escape release cordset 1,5m



570473

PSEN ml escape release cordset 3,0m



570460

PSEN ml escape release



570475

PSEN ml escape release cordset 4,0m