

HAMM0404E



90DEG M20 GLAND 20MM CONDUIT



General Information

Extended Product Type	HAMM0404E
Product ID	7TCA297090R0127
EAN	5011949022652
Catalog Description	90DEG M20 GLAND 20MM CONDUIT
Long Description	Liquid Tight Fitting for Conduit, ATEX Flameproof 90 Degree Elbow Gland, External Male Thread, Conduit Size 20mm, M20 Thread, CSA, Group I & II, Zones 1, 2, 21 and 22, Class I Div2 ABCD, Class II Div1 EFG, Nickel Plated Brass with Epoxy Resin Barrier

Ordering

EAN	5011949022652
Minimum Order Quantity	1 piece
Customs Tariff Number	7412200035

Dimensions

Product Net Weight	0.531 kg
--------------------	----------

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	76.2 mm
Package Level 1 Height	25.4 mm
Package Level 1 Depth / Length	50.8 mm
Package Level 2 Units	10 piece
Package Level 2 Width	355.6 mm
Package Level 2 Height	406.4 mm
Package Level 2 Depth / Length	355.6 mm

Additional Information

Brand / Label	Kopex
Color	Metallic
Function	Ideal for Ex I & II 2 GD Gas and Dust, Exde IIC and Exe II Applications
Insulation Material	IP66 Rating
Material	Brass with Epoxy Resin Barrier

Product Main Type	KOPEX-EX FLEXIBLE CABLE PROTECTION
Product Name	BRASS 90 DEGREE ELBOW FITTING
Product Type	90 Degree Liquid Tight Conduit Fitting with Flameproof Barrier
Standards	CSA 060582, ATEX: Sira 09ATEX1231X, IEC EN 60079-0, 60079-1, 60079-7, 60079-31

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	HAMM0404E
Instructions and Manuals	HAMM0404E

Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121420
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4585 >> Liquid tight connectors

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

